

SAFETY DATA SHEET

Stanley – Blue Chalk

January 27, 2024

Revision 3

1. PRODUCT and COMPANY IDENTIFICATION

Commercial Product Name: Stanley – Blue Chalk

Company: Stanley Black & Decker

Use of product: Snap line, mark

Emergency contact: North America (888) 698-2571; International +1-410-329-9200

2. HAZARDS IDENTIFICATION**Hazards Identification: GHS Classification and Hazard Statement****Carcinogenicity** – May cause cancer (lung) Category 1A, H350**Signal Word: DANGER****Hazard Statements**

H350 May cause cancer

Precautionary Statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves and eye protection.

P308 and P313 If exposed or concerned, get medical advice/attention.

P405 Store locked up.

Hazards Not Otherwise Classified or Not Covered by GHS:**Eye:** May cause irritation. Chalk dust is discomforting and abrasive to the eyes.**Skin:** Prolonged skin contact may cause irritation. When the product is used as intended, it is unlikely to cause discomfort.**Ingestion:** Ingestion of large amounts may cause gastrointestinal irritation. Ingestion is considered an unlikely route of entry in commercial or industrial environments.**Inhalation:** May cause respiratory tract irritation. When the product is used as intended, it is unlikely to cause discomfort.**Chronic:** Repeated and prolonged inhalation exposure to crystalline silica dust above exposure limits may cause delayed, chronic lung injury (silicosis). When the product is used as intended, dust levels should not exceed exposure limits. See Sections 8 and 11.**DANGER****Hazard Ratings:****Hazardous Material Identification System (HMIS):**

Health 1*, Flammability 0, Reactivity 0 *chronic effects

National Fire Protection Association (NFPA):

Health 1, Flammability 0, Reactivity 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Substance name | Value (%) | CAS No. | EC No. |
|--|-----------|------------|-----------|
| Calcium carbonate | 70 - 90 | 471-34-1 | 207-439-9 |
| Sodium aluminosilicate | 10 - 30 | 57455-37-5 | 309-928-3 |
| Crystalline silica (quartz) ¹ | 0.1 - 1 | 14808-60-7 | 238-878-4 |

¹ Calcium carbonate may contain quartz, a form of crystalline silica at levels between 0.1 and 1.0 % and varies naturally.

SAFETY DATA SHEET

Stanley – Blue Chalk

4. FIRST AID MEASURES

Inhalation: Remove from exposure and move to fresh air immediately. Encourage the patient to blow nose to ensure clear breathing passages. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear.

Skin contact: Wet clothing first to minimize dust generation, then; remove contaminated clothing and shoes. Launder contaminated clothing before wearing again. Wash affected area with water (and soap if available) Get medical aid in the event of irritation.

Eye contact: Do not rub eyes, rubbing may cause abrasions. Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Ingestion: Wash mouth out with plenty of water. If the victim is conscious and alert, give 2-4 cupfuls of milk or water. Do not induce vomiting unless directed to do so by medical personnel. Get medical aid immediately.

Additional advice: Show this safety data sheet to the doctor in attendance

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Substance is noncombustible.

Explosion: No information found.

Specific hazards: Not considered to be a significant fire risk, however; the containers may burn, releasing carbon monoxide, and carbon dioxide.

Special protective equipment for Firefighters: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Wear appropriate personal protective equipment as specified in Section 8.

Environmental precautions: Do not allow this material to be released to the environment without proper governmental permits.

Methods for cleaning up: Recover the product whenever possible. Avoid generating dust when sweeping/shoveling up. If required, wet the material with water to prevent creating dust. Pick up and place in a suitable container for reclamation or disposal. Follow applicable OSHA regulations (29 CFR 1910.120)

7. HANDLING AND STORAGE

Storage: Store this product in a tightly closed container in a dry, well-ventilated area away from incompatible substances.

Handling: Avoid creating or breathing dust. Practice good personal hygiene, (hand washing, etc.) after using this product. Avoid contact with skin and eyes.

Packaging material: No information found.

SAFETY DATA SHEET

Stanley – Blue Chalk

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| Component | CAS No. | % by weight | Exposure Limit 8-Hour TWA ¹ (mg/m ³) | | |
|---|------------|-------------|---|----------------------------------|------------------|
| | | | OSHA PEL | ACGIH TLV [®] | Canada OEL |
| Calcium carbonate | 471-34-1 | 70 - 90 | 15 ² , 5 ³ | Not Est. | Not Est. |
| Sodium aluminosilphosilicate-Ultramarine Blue 29 (C.I. 77007) | 57455-37-5 | 10 - 30 | 15 ² , 5 ³ | 10 ² , 3 ³ | 4 ^{2,5} |
| Crystalline silica Quartz ⁴ | 14808-60-7 | 0.1-1.0 | 0.05 ³ | 0.025 ³ | 0.1 ³ |

¹ TWA = Time-weighted average

² Total dust.

³ Respirable dust.

⁴ Calcium carbonate may contain quartz, a form of crystalline silica at levels between 0.1 and 1.0 % and varies naturally.

⁵ Occupational Exposure adopted by the UK Health and Safety Executive.

Exposure and Engineering Controls: Facilities storing or utilizing this material should have potable water available for washing eyes and skin. Use sufficient general area (or outdoor) ventilation. Local exhaust ventilation should be used if airborne concentrations of dust exceed limits cited in Section 8.

Personal protective equipment:

Hand protection: Wear protective gloves

Eye protection: Wear safety glasses, or chemical goggles in windy conditions or where eye contact is possible.

Respiratory protection: When engineering controls are not sufficient to reduce exposure, seek professional advice prior to respirator selection and use. Follow the OSHA respirator regulations found in 29CFR 1910.134 or European Standard EN 149. Always use a NIOSH or European Standard EN 149 approved respirator when necessary.

Hygiene measures: Wash contaminated clothing before reuse.

Environmental exposure controls: No information found.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|--------------------------------------|
| Appearance: | Powder |
| Color: | Blue |
| Odor: | Odorless. |
| pH (at 10% solids): | No data available. |
| Boiling point/range: | No data available. |
| Melting point/range: | Loss of sulfur above 752 °F (400°C). |
| Flash point: | No data available. |
| Evaporation rate: | No data available. |
| Vapor density: | No data available. |
| Solubility in water: | <0.0002 (Trace) |
| Explosive properties: | No data available. |
| Oxidizing properties: | No data available. |
| Vapor pressure: | No data available. |
| Relative density (H ₂ O=1): | 2.68 |
| Viscosity: | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Particle characteristics: | No data available |

SAFETY DATA SHEET

Stanley – Blue Chalk

10. STABILITY AND REACTIVITY

Stability: Stable under normal temperatures and pressures.

Hazardous decomposition products: Hydrogen sulfide gas, Sulfur dioxide, Carbon monoxide, and Carbon dioxide.

Materials to avoid: Acids.

Conditions to avoid: At temperatures above 752 °F in the presence of air, an exothermic chemical reaction can occur with the evolution of sulfur dioxide gas. Contact with acids liberates hydrogen sulfide gas

Hazardous Polymerization: Does not occur.

11. TOXICOLOGICAL INFORMATION

Note: Toxicological effects described in this section are those that would be expected based on data from the components of this product.

Acute toxicity: No data reported.

Inhalation: (Silica, crystalline quartz) Human: LC_{Lo}: 300 µg/m³/ intermittent exposure over a 10-year period produced pulmonary system effects.

Skin contact: (Calcium carbonate) Rabbit: 500mg administered for 24 hours produces moderate skin irritation.

Eye contact: No data reported.

Ingestion: (Ultramarine blue) Rat: LD₅₀: 5,000 mg/kg.

Chronic toxicity/Carcinogenicity: Repeated and prolonged inhalation exposure to crystalline silica dust above exposure limits may cause delayed, chronic lung injury (silicosis). When the product is used as intended, dust levels should not exceed exposure limits.

Crystalline silica – Quartz:

The International Agency for Research on Cancer (IARC) has designated this substance Group 1, “carcinogenic to humans”.

The National Toxicology Program (NTP) has designated this substance: Group K “known to be a human carcinogen”

American Conference of Governmental Industrial Hygienists (ACGIH) has designated this substance A2; suspected human carcinogen. The agent is carcinogenic in experimental animals at dose levels, by route of administration, at sites of histologic type(s) or by mechanism(s) considered relevant to worker exposure. Available epidemiologic studies are conflicting or insufficient to confirm an increased risk of cancer in exposed humans.

12. ECOLOGICAL INFORMATION

Bioaccumulation: No information found.

Ecotoxicity: Sodium aluminosilicate-Pigments are very stable, except under acidic conditions when they will decompose to white siliceous material with the evolution of hydrogen gas. These pigments pose no threat to the environment if disposed of responsibly.

13. DISPOSAL CONSIDERATIONS

Waste from residues of this product is not a hazardous waste according to U.S. Environmental Protection Agency (EPA) regulations. Disposal by landfill may be acceptable.

Consult an expert on the disposal of recovered material for compliance with state, provincial, and/or local regulations.

SAFETY DATA SHEET

Stanley – Blue Chalk

14. TRANSPORT INFORMATION

U.S. DOT: Not regulated

ADR/RID: Not regulated

IMDG: Not regulated

ICAO/IATA: Not regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

OSHA: Ingredients are listed as air contaminants (29 CFR 1910.1000).

Hazardous by definition of the Hazard Communication Standard (29 CFR 1910.1200).

TSCA (Toxic Substance Control Act): All components of this product are listed on the TSCA inventory.

CERCLA: Hazardous Substance, (40 CFR 302.4): Not Listed.
Extremely Hazardous Substance (40 CFR 355): Not Listed.

SARA Hazard Category: This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following category:

"An immediate (acute) and chronic health hazard."

Chemicals subject to the reporting requirements of Section 313 or Title III of SARA and 40 CFR Part 372: None.

STATE REGULATIONS:

California's "Safe Drinking Water and Toxic Enforcement Act of 1986" (Proposition 65)



WARNING: This product contains the following Proposition 65 regulated materials known to the State of California to cause cancer or reproductive harm. The listed typical amounts are a result of their natural presence in the raw materials from which this product is produced.

Crystalline silica- quartz equal to, or less than 1.0 percent.

16. OTHER INFORMATION

The contents and format of this SDS are in accordance with the U.S. Hazard Communication Standard 29 CFR 1910.1200; the Canadian CPR, and Workplace Hazardous Materials Information System (WHMIS); and EEC Commission Directive 1999/45/EC, and EEC Commission Regulation 1907/2006/EC (REACH) Annex II. This product is classified according to Regulation (EC) Number 2020/878.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

End of document